

Novel ammonia production method using both microbubbles and iron electrodes for seawater electrolysis

Yuka Ando, Mitsuki Ishigaki, and Erena Aihara
Shizuoka Kita High School, Japan

Recently, ammonia (NH_3) has been attracting attention as a renewable energy carrier worldwide. The conventional method of producing NH_3 requires high temperatures and pressures that cannot be consistently maintained using renewable energy sources due to the influence of environmental conditions such as the weather.

Although an NH_3 production method using microbubbles (MBs) has been developed at our school, it lacks the high generation rate required for practical use. The NH_3 generation rate achieved using the abovementioned method increased 200 times after conducting electrolysis using a NaCl solution and iron electrodes. This is mostly because ferric hydroxide (III) colloidal particles transport the MBs to the vicinity of the electrodes, thereby leading to the collapse of the MBs and rapid increases in pH and surface tension, resulting in the acceleration of NH_3 generation.

After verifying the proposed mechanism, NH_3 generation was optimized, and various iron nitrides were produced using a 6–15% (w/v) NaCl solution with a pH of ≥ 12 , an electric current of ≥ 0.3 A, and N_2 flow rate of ≥ 1 L/min.

The study findings demonstrate that high-efficiency NH_3 generation from renewable energy is achievable via an ammonia production device embedded with an iron multi-electrode system, where cathodes and anodes are periodically reversed, converting nitriding iron to NH_3 .

(207 words)